



POLI-FLEX® PREMIUM



160°C
130°C BLOCKOUT SOFT



15 SEC
5 SEC BLOCKOUT SOFT



2,5 - 3,0 BAR



WARM
LUKE WARM



80°C
TUMBLE DRY
DRY CLEANING



MULTI LAYER



OEKO-TEX®
CONFIDENCE IN TEXTILES
STANDARD 100
14.0.44284 HOHENSTEIN HTTI
Tested for harmful substances.
www.oeko-tex.com/standard100



500 MM X 25 M
500 MM X 10 M
1000 MM X 25 M
1524 MM X 25 M

Please find detailed information in the technical data sheets | Detaillierte Informationen entnehmen Sie den technischen Datenblättern

#BeCreative



YouTube



POLI-FLEX® TURBO
POLI-FLEX® PREMIUM
POLI-FLEX® PEARL GLITTER
TUBITHERM® FLOCK
POLI-FLEX® IMAGE
POLI-FLEX® BLOCKOUT SOFT
POLI-FLEX® NYLON
POLI-FLEX® SPORT
POLI-FLEX® STRETCH
POLI-FLEX® PRINTABLE
TURBO PRINT
ULTIMATE PRINT



HEAT TRANSFER VINYL'S 4 every challenge



TURBO PRINT 4036 MATT is the printable polyurethane transfer vinyl equipped with the same special hotmelt and features like POLI-FLEX® TURBO

TURBO PRINT 4036 MATT ist die bedruckbare Polyurethan Transferfolie mit dem selben speziellen Heischmelzkleber und Eigenschaften wie POLI-FLEX® TURBO



POLI-TAPE Klebefolien GmbH

Zeppelinstrae 17
53424 Remagen - GERMANY

Telefon: +49 2642 98 36 0
Fax: +49 2642 98 36 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

Your POLI-TAPE products distributed by

ALPHASET

TECHNOLGIE A MATERILY NA VROBU REKLAMY
ALPHASET spol. s r.o., Kopianska 19, 851 01 Bratislava
Tel: +421 2 6381 2255 • Mobil: +421 918 656 524
e-mail: alphaset@alphaset.sk

www.alphaset.sk www.rolanddga.sk
www.frezy.sk www.i-mark.sk